



# Specification

Le Menu: Beilagen Spezifikationen



## Specification: Beilagen Spezifikationen

---

### Specifications

(Detaillierte technische Spezifikationen nach Rücksprache erhältlich)

#### 1 - BEILAGEN

##### Platzierung

im hinteren Drittel der Zeitschrift an unbestimmter Stelle (da Adressierung über 4. US erfolgt) oder Zwischen der letzten Seite Inhalt und der 3. US

##### Format

Minimum 105 x 148 mm

Maximum 200 x 265 mm ideal (200 x 275 mm auch möglich)

##### Umfang

Minimum 2 Seiten

Maximum 32 Seiten, Dicke: 2 mm

#### 2 - BEIHEFTER/MITBINDER

##### Platzierung

zwischen 2 Bogenteilen

##### Format

Minimum 105 x 148 mm

Maximum 210 x 275 mm

##### Umfang

Minimum 2 Seiten

Maximum 32 Seiten

##### Beschnitt

4 mm Kopfbeschnitt

3 mm Fräsrund

#### 3 - AUFKLEBER

##### Platzierung

auf Titelseite oder erste Seite eines 16er Bogens

##### Format

Minimum 70 x 70 mm

(kleiner Formate auf Anfrage)

Maximum 180 x 225 mm

##### Umfang

Minimum 2 Seiten

Maximum 24 Seiten

### Technical specifications

#### Technical specifications



Bleed ads: add 3 mm for bleed on all four edges. Keep all matter that must not be trimmed within a safety margin of 8 mm from final trim size.

Position of type area: margins: face 12 mm, gutter 15 mm, head 15 mm, foot 16 mm.

Where text or graphic elements extend across the gutter, to avoid them being concealed by the adhesive binding, a safety margin of 10 mm should be observed.

[nbsp]

#### **Print documents**

Only digital delivery of documents possible. The standard data delivery format is a PDF file. This is preferred to delivery of other file formats.

[nbsp]

#### **Data delivery**

All transferred data must include the title, issue number, customer name and a keyword for the subject (e.g. annabelle15\_customer\_keyword.pdf).

[nbsp]

#### **Ready-to-print digital templates**

PDF format: High-end PDF (embedded fonts). Settings: <http://www.pdfx-ready.ch>

Format/positioning: The document size should match the correct positioning of the advertising space paid

Images: CYMK (no RGB color space)

Image resolution: 300 dpi

[nbsp]

Please note: files not meeting the stated specifications will have to be resubmitted.

[nbsp]

#### **Data transfer**

E-Mail [anzeigen@annabelle.ch](mailto:anzeigen@annabelle.ch)

[nbsp]

#### **Printing data**

Print process: Roll offset

Screen count: 60 frames

Profile content paper: PSO\_LWC\_Improved (ECI)

Dot shape: Elliptical

Starting tone: 4%

Total UCR: 280–300%

Colours: Euroscale

Grey balance: to ISO standard

Dot gain: to ISO standard

Test tools: Ugra/Fogra media wedge

Trim: 3 mm

Spectrophotometer: GretagMacbeth Spectrolino/Spectroscan, SpectroEye

### **Delivery**

[nbsp]

#### **Print documents**

Only digital delivery of documents possible. The standard data delivery format is a PDF file. This is preferred to delivery of other file formats.

[nbsp]

#### **Data delivery**

All transferred data must include the title, issue number, customer name and a keyword for the subject (e.g. annabelle15\_customer\_keyword.pdf).



[nbsp]

**Ready-to-print digital templates**

PDF format: High-end PDF (embedded fonts). Settings: <http://www.pdfx-ready.ch>

Format/positioning: The document size should match the correct positioning of the advertising space paid

Images: CYMK (no RGB color space)

Image resolution: 300 dpi

[nbsp]

Please note: files not meeting the stated specifications will have to be resubmitted.

[nbsp]

**Data transfer**

E-Mail [anzeigen@annabelle.ch](mailto:anzeigen@annabelle.ch)

[nbsp]